

BE - BRASS EXPANSION ANCHOR

Light to Medium duty anchor for use in solid brickwork, blockwork, hard stone, concrete and wood.

Ideal for carpentry joints, hand rails, seating and where the structural thickness is restricted. Will accept bolts, stud screws and studding.



Size d x L	Code	Price Per 100	L	d	do	hnom	h1 min	Lv min	Frec kN	Box qty	Outer
M5x25	BE0525	£32.89	20	M5	6.5	20	25	13 + tfix	1.1	100	1000
M6x23	BE0630	£45.36	23	M6	8	23	30	23 + tfix	1.4	100	1000
M8x35	BE0835	£74.16	28	M8	10	28	35	28 + tfix	2.17	100	1000
M10x33	BE1040	£110.59	33	M10	12	33	40	33 + tfix	2.62	100	1000
M12x38	BE1243	£176.90	38	M12	15	38	43	38 + tfix	3.42	100	1000

L	Anchor Body Length (mm)
d	Anchor Thread Length (mm)
do	Drill hole diameter (mm)
hnom	Anchor Embedment depth (mm)
h1	Deep of drilled hole deepest point (mm)
Lv min	Minimum bolt length (mm)
Frec	Recommended Tensile/Shear Load (kN)

Recommended loads (Frec) in concrete C25

All dimensions in mm, unless otherwise stated.

